



PRODUCT-DETAILS

# OTDCP32S22M

## OTDCP32S22M Enclosed solar switch



General Information	
Extended Product Type	OTDCP32S22M
Product ID	1SCA125093R1001
EAN	6417019553498
Catalog Description	OTDCP32S22M Enclosed solar switch
Long Description	The enclosure in the OTDCP series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables, both from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked, and the interlock can be defeated with a special tool. Typical applications is solar panels, DC batteries, etc.

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC301240D0201
RoHS Information	1SCC301239D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC301321D0201

---

## Ordering

---

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

---



---

## Popular Downloads

---

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340027M0002
Mechanical Drawings	OTDCK159595SM20.stp

---



---

## Dimensions

---

Product Net Width	95 mm
Product Net Height	150 mm
Product Net Depth / Length	95 mm
Product Net Weight	0.63 kg

---



---

## Technical

---

Rated Operational Current DC-21B ( $I_e$ )	(1000 V) 32 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 32 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V AC) 0.71 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 0.5 kA
Power Loss	at Rated Operating Conditions per Pole 0.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Selector handle
Standards	IEC 60947-1, -3
Special Functions	Solar
Mounting Type	Base mounting
Number of Poles	4
Connecting Capacity Main Circuit	Screw Clamp 2.5...16 mm <sup>2</sup>
Wire Stripping Length	Main Circuit 29 ... 11 mm
Recommended Screw Driver	Main Circuit Torx
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xM20 / 2xM20
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Mounted Auxiliary Contacts	0 NO, 0 NC
Tightening Torque	Main Circuit 1.2 ... 1.4 N·m

---

---

## Technical UL/CSA

---

Wire Stripping Length	Main Circuit 29 ... 11 mm
Recommended Screw Driver	Main Circuit Torx
Tightening Torque	Main Circuit 1.2 ... 1.4 N·m

---



---

## Certificates and Declarations

---

BV Certificate	1SCC340018D0204
Declaration of Conformity - CE	1SCC340003D2704

---



---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	142 mm
Package Level 1 Depth / Length	167 mm
Package Level 1 Height	108 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	6417019553498

---



---

## Classifications

---

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601739
E-Number (Norway)	1414593
E-Number (Sweden)	3134015

---



---

## Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

