



PRODUCT-DETAILS

DR E2N/MS 1250 4p to E2.2/MS int

DR E2N/MS 1250 4p to E2.2/MS int

General Information

Extended Product Type	DR E2N/MS 1250 4p to E2.2/MS int
Product ID	1SDA113040R1
EAN	8056221029612
Catalog Description	DR E2N/MS 1250 4p to E2.2/MS int
Long Description	Direct Replacement E2N/MS 1250 4p to E2.2/MS - Service customization

Eco Transparency

Environmental Product Declaration - EPD	1SDH002338A1001
---	-----------------

Technical

Standards	IEC
Current Type	AC
Rated Voltage (U _r)	690 V
Rated Operational	690 V AC

Voltage

Rated Current (I _n)	1250 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 55 kA
Number of Poles	4
Version	W
Configuration Type	Mounted only
Product Type	Direct Replacement ABB Emax, New Emax to Emax 2 IEC
Sub-type	E2.2

Material Compliance

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108466A1425
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Dimensions

Product Net Width	400 mm
Product Net Height	418 mm
Product Net Depth / Length	393 mm

Ordering

EAN	8056221029612
-----	---------------

Installation

Instructions and Manuals	1SDH002028A1001
Wiring Diagram	1SDM000004A1001 1SDM000004A1002

Popular Downloads

Data Sheet, Technical Information	1SDC001052L0201
-----------------------------------	-----------------

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362090

Additional Information

Product Main Type	Low Voltage retrofit with Emax 2
-------------------	----------------------------------

Categories

Low Voltage Products and Systems → Service → Extensions, Upgrades and Retrofits → Retrofits