



PRODUCT-DETAILS

DR LJ20C 2000 4p to E4.2/MS int**DR LJ20C 2000 4p to E4.2/MS int****General Information**

Extended Product Type	DR LJ20C 2000 4p to E4.2/MS int
Product ID	1SDA121026R1
EAN	8056221156165
Catalog Description	DR LJ20C 2000 4p to E4.2/MS int
Long Description	Direct Replacement LJ20C 2000 4p to E4.2/MS - Service customization

Technical

Standards	IEC
Current Type	AC
Rated Voltage (U_r)	690 V
Rated Operational Voltage	690 V AC
Rated Current (I_n)	2000 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA
Number of Poles	4

Version	W
Configuration Type	Mounted only
Product Type	Direct Replacement GE EntelliGuard L to Emax 2 IEC
Sub-type	E4.2

Material Compliance

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108466A1425
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Dimensions

Product Net Width	538 mm
Product Net Height	374 mm
Product Net Depth / Length	376 mm

Ordering

Package Level 1 Units	pallet (lift) 1 piece
EAN	8056221156165

Installation

Instructions and Manuals	1SDH002096A1001
Wiring Diagram	1SDM000047A1001

Popular Downloads

Data Sheet, Technical Information	1SDC200118L0201
-----------------------------------	-----------------

Classifications

WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362090

Additional Information

Product Main Type	Low Voltage retrofit with Emax 2
-------------------	----------------------------------

Categories

Low Voltage Products and Systems → Service → Extensions, Upgrades and Retrofits → Retrofits