AF31FDTUW 1/3



PRODUCT-DETAILS

AF31FDTUW

Front



General Information	
Global Commercial Alias	AF31FDTUW
Extended Product Type	AF31FDTUW
Product ID	1TQR331235F2000
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

Dimensions	
Product Net Width	31.250 in
Product Net Height	32.750 in
Product Net Depth / Length	0.100 in
Product Net Weight	31.000 lb

Ordering

AF31FDTUW 2/3

Package Level 1 Unitsbox 1 piecePackage Level 1 Gross40.480 lbWeight40.480 lb

Certificates and Declarations

Declaration of No declaration needed Conformity - CE

Installation

Instructions and No document needed Manuals

Popular Downloads

Data Sheet, Technical No document needed Information

Classifications

Product Not in WEEE Scope
39121321
4465 >> Enclosure General Accessories

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow ReliaGear\ Lighting\ Panels$









Subject to change without notice

AF31FDTUW 3/3



