



 PRODUCT-DETAILS

AF82SPTNMW

Front



General Information

Global Commercial Alias	AF82SPTNMW
Extended Product Type	AF82SPTNMW
Product ID	1TQR382135D1300
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product Declaration - EPD	1SQC173004D0201

Dimensions

Product Net Width	30.000 in
Product Net Height	82.500 in
Product Net Depth / Length	0.100 in
Product Net Weight	77.000 lb

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	98.870 lb

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications

WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

Categories

Low Voltage Products and Systems → NEMA Residential and Commercial Portfolio → Lighting Panels & Breakers → ReliaGear Lighting Panels

