T2453 AN 1/3



PRODUCT-DETAILS

## **T2453 AN**

## Surface works. w/cover 3XSO AN Anthracite - CEM



General Information	
Extended Product Type	T2453 AN
Product ID	2CLA245300T180
EAN	842723814352
Catalog Description	Surface works. w/cover 3XSO AN Anthracite - CEM
Long Description	3 socket outlets fully wired with 2,5mm2 halogen free cable Power input through cable with male rapid connector at end High fixation with black lacquered support Mounted on aluminium profile black lacquered Structure made of aluminium profile Opening by means of 90° turn with locking and auto-return

Installation	
Instructions and Manuals	No document needed

## **Environmental**

T2453 AN 2/3

Ambient Air Operation -5 ... +35 °C Temperature Storage -5 ... +50 °C

Technical	
Data Sheet, Technical Information	No document needed
Number of Connections	Number of audio connections: 0
	Number of CAT 5 connections: 0
	Number of CAT 5E connections: 0
	Number of CAT 6 connections: 0
	Number of HDMI-connections: 0
	Number of USB connections: 0
Number of Empty	0
Module Positions	
Number of Batteries	0

Design	
Design Range	СЕМ
Shape	Rectangular
Material	Aluminium
Color	Anthracite

Dimensions	
Product Net Width	229.5 mm
Product Net Height	82 mm
Product Net Depth / Length	82 mm
Product Net Weight	1.218 kg

Material Compliance	
RoHS Information	2CLC245300T1801
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108467A7464
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20230816
Conflict Minerals Reporting Template	9AKK108468A3363

Certificates and Declarations	
Declaration of	No declaration needed
Conformity - CE	

Classifications	
ETIM 9	EC002759 - Desk connecting unit
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

T2453 AN 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Flush\ Mounted\ Inserts \rightarrow Socket\ Outlets$ 

