

PRODUCT-DETAILS

# ACQ531-01-062A-4+0J404

ACQ531-01-062A-4+0J404 PN: 30kW, IN: 62A



General Information	
Global Commercial Alias	ACQ531-01-062A-4+0J404
Product ID	3ABD00049853
ABB Type Designation	ACQ531-01-062A-4+0J404
Catalog Description	ACQ531-01-062A-4+0J404 PN: 30kW, IN: 62A
Long Description	The ACQ531-01 drives deliver innovative pump features for the water and wastewater industry, securing energy efficient flow of water and wastewater in your pumping solutions. This robust and compact wall-mounted drive has built-in simple pump application functionality. Usability is further enhanced with the optional intuitive Hand -Off-Auto control panel, the PC tool Drive composer and an optional Bluetooth® control panel. The built-in energy calculator visualizes the energy savings achieved with the use of the drive. The ACQ531-01 variant comes in an IP20 enclosure as standard and can be installed on the wall.

Ordering	
Country of Origin	China (CN)
Customs Tariff Number	85044099
Invoice Description	ACQ531-01-062A-4+0J404 PN: 30kW, IN: 62A
Made To Order	No

Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions	
Product Net Weight	18.5 kg
Product Net Depth / Length	257 mm
Product Net Height	636 mm
Product Net Width	203 mm
Package Level 1 Depth / Length	720 mm
Package Level 1 Height	380 mm
Package Level 1 Width	300 mm
Package Level 1 Units	1 carton

Technical	
Number of Phases	3
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Frequency (f)	47.5 63 Hz
Frame Size	R4
Input Voltage (U <sub>in</sub> )	380 480 V
Mounting Type	Module_NO UNIT\$
Output Current, Light-	58 A
Overload Use ( $I_{LD}$ )	
Output Current, Normal	62 A
Use $(I_n)$	
Output Power, Light-	30 kW
Overload Use ( $P_{LD}$ )	
Output Power, Normal	30 kW
Use $(P_n)$	
Efficiency Level	IE2
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	241 W	0.6 %	90.4 %
0 / 50 %	316 W	0.7 %	93.3 %
0 / 100 %	569 W	1.3 %	93.9 %
50 / 25 %	264 W	0.6 %	94.7 %
50 / 50 %	364 W	0.8 %	96.2 %
50 / 100 %	677 W	1.6 %	96.4 %
90 / 50 %	424 W	1 %	97.5 %
90 / 100 %	867 W	2 %	97.4 %

# Classifications

ACQ531-01-062A-4+0J404 3/3

UNSPSC 39122001

### **Environmental**

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

#### **Additional Information**

Product Name Frequency Converter

# **Categories**

 $\mbox{Drives} \rightarrow \mbox{Low Voltage AC Drives} \rightarrow \mbox{Industry-Specific Drives} \rightarrow \mbox{Drives for Water} \rightarrow \mbox{ACQ531-01} - \mbox{Wall-mounted drive for water and wastewater}$ 

