




---

 PRODUCT-DETAILS

# 3GBP132323-BDBCNZB

## No Description Available

---

**General Information**

Product ID	3GBP132323-BDBCNZB
ABB Type Designation	M3BP 132SMC 4
Catalog Description	No Description Available

---

**Additional Information**

ABB Type Designation	M3BP 132SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6308-RS/C3
Bearing NDE	6308-RS/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

**Electrical Data**

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	7.50 kW	1450 r/min	8.60 A	0.810	89.30 %	49.30 N·m	5.60
D	--	50 Hz	400 V	7.50 kW	1450 r/min	14.90 A	0.810	89.30 %	49.30 N·m	5.60
D	--	60 Hz	460 V	7.50 kW	1760 r/min	12.60 A	0.820	90.60 %	40.60 N·m	6.70

Frame Material	Cast Iron
Frame Size	132
Gross Weight	74 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 89.3 % Partial Load (75%) 90.1 % Partial Load (50%) 90.0 %
IM Class	IMV1 IM3011
IP Class	IP55
Insulation Class	ICLF
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4

Order Multiple	1 piece
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	73 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)