




---

 PRODUCT-DETAILS

# 3GJA282101-HDDX

## M2JAX 280S4A

---

**General Information**

Product ID	3GJA282101-HDDX
ABB Type Designation	M2JAX280S4A
Catalog Description	M2JAX 280S4A

---

**Additional Information**

ABB Type Designation	M2JAX280S4A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	China (CN)
Customs Tariff Number	85059090
Direction of Rotation	Both sides

**Electrical Data**

Conn	Temp Class	Freq	Voltage	Power
D	T4	50 Hz	380-400 V	75.00 kW
Y	T4	50 Hz	660-690 V	75.00 kW
D	T4	60 Hz	460 V	86.00 kW

Frame Material	Cast Iron
Frame Size	280
Gross Weight	803 kg
IC Class	IC411
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2JAX 280S4A
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece

Product Name	3 PHASE
Product Net Weight	765 kg
Product Type	2JAX_M2JAX_IE2_Flameproof_Ex_d_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	T4
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)