



 PRODUCT-DETAILS

CDRX32424T-5

Explosion Proof Drill Rig Duty 40 Hp 575 V (CDRX32424T-5)



General Information

Global Commercial Alias	CDRX32424T-5
Product ID	7BCDRX32424T-5
ABB Type Designation	40HP,3540RPM,3PH,60HZ,324TSC,XPFC,F
Catalog Description	Explosion Proof Drill Rig Duty 40 Hp 575 V (CDRX32424T-5)

Ordering

ABB Type Designation	40HP,3540RPM,3PH,60HZ,324TSC,XPFC,F
Invoice Description	40HP,3540RPM,3PH,60HZ,324TSC,XPFC,F1
Product Name	Explosion Proof Drill Rig Duty
Product Type	Undefined
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	United States (US)
Customs Tariff Number	85015230
Stocked At	China

(Warehouses)

Alabama, United States
Alaska, United States

Medium Description	Explosion Proof Drill Rig Duty, 40 HP, 3600 RPM, Frame Size 324Tsc, C-Face Mounting, 3 Phase, XPFC Enclosure, 575 V, 60 Hz (CDRX3242
Short Description	40 HP, 3600 RPM, Frame Size 324Tsc, C-Face, 3 PH, XPFC, 575 V

Electrical

Electrical Data

	Current	Freq	Power	Speed	Voltage
	36 A	60 Hz	40 Hp	3540 r/min	575 V
Frequency (f)					60 Hz
Output Power					40 Hp
Ambient Temperature					40 °C
Insulation Class					F
Number of Poles (High)					2
Type of Duty					Continuous

Mechanical

Frame Material	Iron
Frame Size	Undefined

Dimensions

Product Net Depth / Length	40.625 in
Product Net Height	25.625 in
Product Net Width	32.5 in
Product Net Weight	745 lb
Gross Weight	745 lb

Classifications

Standards	NEMA
-----------	------

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Explosion Proof Motors → Drill Rig Duty, 1.15 SF Motors

