

Item	Qty	Description of products and services	Price per unit	Amount
------	-----	--------------------------------------	----------------	--------

1

1

		<p>Commissioning Power Supply, 28 V DC, 30 mA</p> <p>The commissioning power supply generates a DC voltage and is used for on site commissioning of KNX devices should KNX system voltage be unavailable. Hence, the most important functions of a KNX device (e.g. Fan Coil Actuator FCA/S) can be tested with manual operation. The output of the device is permanently short-circuit proof and overload protected.</p> <p>Supply Voltage 85 ...285 V AC, 45...65 Hz</p> <p>Nominal Voltage 21...28 V DC, SELV</p> <p>Nominal Current 30 mA</p> <p>Connection</p> <p> Voltage input EURO connector in accordance with EN 50075, VDE 0620-1</p> <p> Voltage output Plug-in screw terminal Core cross-section 0.2...1 mm²</p> <p>Display elements LED green: In operation LED red: Error</p> <p>Type of protection IP 20, EN 60 529</p> <p>Dimensions 55.5 x 55 x 25.5</p> <p>Manufacturer ABB STOTZ-KONTAKT</p> <p>Type NTI/Z 28.30.1</p> <p>Material: Labour: ...</p>	Carry:	
--	--	--	--------	--

		NTIZ_28301_AT_EN_V2-0 2CDC 501 038 D0201	Carry:	
--	--	---	--------	--

NTI/Z 28.30.1

NTI/Z 28.30.1