

TECHNICAL DATA SHEET

Terminals, lipped blade

Vinyl-insulated, double crimp

Spec-Kon®



Vinyl-insulated lipped blade terminals for wire termination of copper conductors ranging from 0.5mm² to 6mm²

Certifications / Standards:



Features:

- Easy entry double crimp
- Corrosive resistant plating
- Color coded to wire size range

Maximum rating:

- 75°C Max
- 600 volts
- Copper conductors only

Application tool:

- ERG9004

Conforms to:

- IEC 60352-2

Materials / Finishes:

- Copper terminal
- Electro-Tin plated
- Vinyl insulation

Product selection

Drawing	Part no:	Wire size range (mm ²)	Color	Dimensions (mm)				Crimping tool
				L	F	W	D	
	LB1.5-3VDC	0.5 - 1.5	Red	25.7	16.8	3.0	4.3	ERG9004
	LB1.5-46VDC	0.5 - 1.5	Red	25.7	16.8	4.6	4.3	
	LB2.5-3VDC	1.5 - 2.5	Blue	25.7	16.8	3.0	4.8	
	LB2.5-46VDC	1.5 - 2.5	Blue	25.7	16.8	4.6	4.8	
	LB6-3VDC	4.0 - 6.0	Yellow	30.2	17.2	3.0	6.7	
	LB6-46VDC	4.0 - 6.0	Yellow	30.2	17.2	4.6	6.7	

Note: Products must be installed in accordance with applicable national and local electrical codes.