

PRODUCT BROCHURE

T&B[®] Fittings XD expansion/deflection coupling for rigid conduit

T&B Fittings



A better solution for expansion/deflection coupling of rigid metal conduit

Use the T&B® Fittings XD expansion/deflection coupling to join two conduit runs in applications where movement in any direction is required. The coupling provides a flexible, watertight connection, accommodating axial or parallel movement of up to ¾" and angular movement of up to 30° from normal position.

While similar fittings exist on the market today, this XD expansion/deflection coupling ships complete with an Erickson® type conduit union to significantly reduce installation time and effort. It also includes a stainless steel inner sleeve for extreme durability, protection and easier wire pulling. The hubs are zinc-plated and coated with aluminum acrylic paint for dual-layer corrosion protection. In addition, the copper ground mounting plates and internal grounding bonding jumper are entirely enclosed inside the coupling for added security against vandalism and theft.

Features:

- Accommodates axial or parallel movement of up to ¾" and angular movement of up to 30° from normal position
- Suitable for use indoors, outdoors, direct buried or embedded in concrete
- Watertight, flexible neoprene outer jacket, zinc-plated and acrylic-painted hubs and stainless steel tamper-proof straps ensure superior corrosion resistance—ideal for use in harsh environments
- Copper ground mounting plates and internal grounding bonding jumper both entirely enclosed to safeguard against theft
- Includes an Erickson type conduit union for faster, easier installation to reduce labor costs
- Durable stainless steel inner sleeve provides a constant, smooth inner diameter in any position to ease wire pulling and protect wire insulation from damage
- NPT threaded hubs fit standard threaded rigid metal conduit
- Can also be used with rigid PVC conduit with the use of standard adapters (not supplied)

Standard materials/finishes:

- Hub
 - Cast iron, zinc-plated and painted with aluminum acrylic paint
- Inner sleeve
 - Stainless steel
- Internal grounding bonding jumper
 - Flexible copper braid
- Ground mounting plates
 - Copper
- Hub rings
 - Zinc-plated steel
- Outer jacket
 - Molded elastomer (natural black)
- Jacket straps
 - Stainless steel



Why choose the T&B® Fittings expansion/deflection coupling?


- Erickson® type conduit union
 - Included union significantly speeds up installation, reducing your labor costs.
- Stainless steel inner sleeve
 - Stronger and more durable than plastic tubes or corrugated hose and better able to withstand friction from pulling ropes. Provides a smooth transition to ease wire pulling and reduce chance of damage to wire insulation.
- Enclosed copper ground mounting plates
 - Totally enclosed and secured with tamper-proof stainless steel jacket straps for protection against vandalism and theft.
- Dual-layer corrosion-protected hubs
 - Zinc-plated and coated with aluminum acrylic paint for extra corrosion resistance.

Typical applications:

- Bridges
- Tunnels
- Inter-building walkways
- Docks and piers
- Wastewater and water treatment facilities
- Any other application in which conduit runs are subject to movement due to external forces or temperature changes

Certifications/compliances:

- UL listed to UL 514B and CSA certified to C22.2 No. 18 suitable for wet locations (hub sizes 1"–2½")
- Watertight
- NEC Article 250.98 compliant



XD expansion/deflection coupling for rigid conduit



Cat. no.	Hub size (in.)	Dimensions (in.)				Std. pkg. qty.	UPC no.
		A	B	C	D		
XD3-TB	1	9 ¹³ / ₁₆	8 ¹⁵ / ₃₂	6 ⁷ / ₁₆	3 ¹¹ / ₃₂	1	786209-89405
XD4-TB	1 ¹ / ₄	9 ³ / ₁₆	8 ³ / ₈	6 ⁷ / ₈	3 ³ / ₈	1	786209-89414
XD5-TB	1 ¹ / ₂	9 ³ / ₄	8 ⁷ / ₃₂	6 ³ / ₄	4 ⁵ / ₃₂	1	786209-89415
XD6-TB	2	9 ³ / ₄	8 ²¹ / ₃₂	7 ¹ / ₄	4 ¹¹ / ₁₆	1	786209-89416
XD7-TB	2 ¹ / ₂	11 ³ / ₄	11 ³ / ₈	8 ¹ / ₂	4 ⁷ / ₈	1	786209-89417
XD8-TB	3	10 ¹ / ₂	9 ²¹ / ₃₂	7 ²¹ / ₃₂	5 ¹ / ₈	1	786209-89418
XD9-TB	3 ¹ / ₂	10 ⁹ / ₁₆	9 ³ / ₄	7 ³ / ₄	6 ⁵ / ₈	1	786209-89419
XD010-TB	4	13 ³ / ₁₆	11 ²⁷ / ₃₂	8 ⁷ / ₈	7 ⁹ / ₃₂	1	786209-89420
XD012-TB	5	14	12 ¹⁵ / ₁₆	11	8 ⁹ / ₃₂	1	786209-89421
XD014-TB	6	14 ³ / ₁₆	13 ³ / ₈	11 ³ / ₈	9 ¹⁹ / ₃₂	1	786209-89422

Diagrams




ABB Installation Products Inc.
 Electrification Business
 860 Ridge Lake Blvd.
 Memphis, TN 38120

ABB has made every attempt to ensure the accuracy and reliability of the contents of this document. However, all content is provided for general informational purposes only, and ABB makes no guaranty or warranty, express or implied, as to the accuracy of any technical content, or that the information contained in this publication will be error free and all such guarantees or warranties are expressly disclaimed. ABB may change or modify

the contents at any time, without prior notice. We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction or utilization of its contents — in whole or in parts — is forbidden without prior written consent of ABB.
 © 2023 ABB Installation Products Inc. and/or its affiliated companies.
 All rights reserved.